

# APPLICATION TAPE -APT 400

---

A standard weight latex saturated paper designed for protective masking of wide format digital graphics and large vinyl graphics. A medium tack Acrylic adhesive system designed for large transferring graphics and for short- or longterm protection of large digital prints. The stable adhesive will not build over time and will remove easily from the printed graphic upon removal of the premask.

## TECHNICAL DATA.

Colour



White/Translucent

Adhesion to Steel-20 min

250±20 gms/inch (FTM-1)

Paper Thickness



60±10 µ (Screw-gauge)

Total Tape Thickness



80±15 µ (Screw-gauge)

Tensile Strength



>15 mpa

Application Temperature



+10 to +30 °C

Service Temperature

+20 to +90 °C

All Tolerance on the above values to be taken as (±5%) unless specified

## Features:

- Remove easily following graphics application
- If adhesive touches adhesive , perform pull apart easily no adhesive delamination
- work well either or dry application with no adhesive transfer
- No adhesive transfer from the application tape to the vinyl graphics
- Protective tape of large wide format digital graphics / printed and unprinted vinyl graphics

---

We are warrantees our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. We only warrantees our products to be free from defects in workmanship or defects in material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise, shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith.

**Trans/Rite**

PAPER APPLICATION TAPE